DB HiTek

World Leader In Specialty Foundry





Company Overview

Established

1997

• Revenue(2016)

US\$667M

Asset(2016)

US\$817M

Number of Employees

2,100 (Jan. 2017)

Business Areas


System IC


Technology

90nm~0.35um

Capacity

116,000wfs/month (200mm)








Financial Information

Consecutive revenue and margin growth from 2013



History



Management Team



Changsik Choi, CEO



KS Cho, Senior VP, Foundry Business



CH Choi VP, Brand Business



YJ Lee, Senior VP, Technology Development



YG Choi, VP, Manufacturing



WS Kim, VP, QRA



JH Kang, VP, Product Engineering



GH Koo CFO, Senior VP, Strategy Planning


Facilities




Capacity

Continue to expand the capacity

(Unit: Kwfs/month)



Global Networks



Certifications







ESH Certification




Security Certification











(Source: IHS '16.4Q)






(Source: IHS '16.4Q, Gartner '16.4Q, Credit Suisse '16.1, Yuanta Investment Consulting '16.12, DBH Estimation)

Foundry Value Proposition

DB HiTek support customers with valuable benefits



Key Process Portfolio

Analog & Power

- Tech Node: 0.13um ~ 0.35um
- Device Performance (Low Rdson)
- Higher BVdss & SOA

CMOS Image Sensor

- Tech Node: 90nm ~ 0.18um
- Low Power Process
- Low Noise, Low Dark Current,High Sensitivity Process

High Voltage CMOS

- Tech Node: 0.11um ~ 0.35um
- Low Power Process
- Competitiveness Cost Process

Mixed Signal

- Tech Node : 90nm ~ 0.18um
- 90nm, 0.11um Low Noise,Low Leakage
- Available of RF Process (HRS)

Embedded Flash

- Tech Node: 0.13um
- Low Power Process
- Various Macro IP Support

New Technology

- MEMS : Microphone
- SJMOSFET: 600V/650V/700V
- RF CMOS (HRS/SOI)


www.dbhitek.co.kr | CORPORATE PRESENTATION | © 2017

High


Performance

Low Cost

Technology Roadmap



Technology Roadmap



Design Environment

Design Infra

- SPICE Modeling
- PDK/iPDK
- **ESD** solution
- IO/STD cell Library
- Memory Complier



Application Specific IP

Non Volatile Memory (OTP, MTP)

Reference Design Flow

- **Analog/ Mixed Signal Design**
- **Digital Design**
- **EDA Solution**

Partner Companies
















YourFabTM Service

⊕ YourFab[™] LOGIN



ShuttleChip™ Service (2017)

Tape-out start	date
•	

				2017										
Process	Tech	Fab	1Q			2 Q			3 Q			4Q		
			Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
BCD (BD180LV)	0.15um	FAB1							19				08	
Analog / BCD/ Mixed-Signal (AN180 &BD180 & HP180 &MS180)	0.18um		18	22	29	26	31	28	26	30	27	25	29	27
Mixed-Signal	0.11um	FAB2	18			26			26			25		
Analog /BCD (BD130)	0.13um			15		19		21		23		18		20
e-Flash	0.13um						17						15	
Mixed-Signal	0.15 ~ 0.18um				08			07			06			06
HVCMOS	0.11um					19				23				
CIS	0.11um							21				18		

^{* 1.} The shuttle schedule might be changed or canceled if the minimum number of paid seat has not been filled.

^{* 2.} Schedule for some ShuttleChip may change due to un-foreseen circumstances, so please contact your account manager for updated schedule.

^{* 3.} DB check will be cleared within 7 days before tape-out.

ShuttleChip™ Service (2018)

Mixed-Signal

0.18um

												Таре	-out star	t date	
			2018												
Process	Tech	Fab		1Q			2Q			3Q			4Q		
			Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
BCD (BEOL 0.15um, BD180LVA)	0.15um		24			11			11		12		14		
Analog / BCD/ Mixed-Signal (AN180 &BD180 & HP180 &MS180)	0.18um	FAB1	31	28	28	25	23	27	25	29	19	24	28	26	
Mixed-Signal/ RF HRS	0.11um		17			25			25			24			
CIS	0.11um							27				31			
Analog /BCD (BD130)	0.13um	FAB2		21			16			22			21		
	0.15~														

05

07

^{* 1.} The shuttle schedule might be changed or canceled if the minimum number of paid seat has not been filled.

^{* 2.} Schedule for some ShuttleChip may change due to un-foreseen circumstances, so please contact your account manager for updated schedule.

^{* 3.} DB check will be cleared within 7 days before tape-out.



THANK YOU

